Safety Data Sheet

Printing date 03/26/2021 Revised On 03/26/2021

1 Identification of the substance and manufacturer

Trade name: ORANGE
Product code: STOR1SD

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Manufacturer/Supplier: Fox Valley Paint 5A Production Drive Brookfield, CT 06804 phone: 844-627-5255

email: info@foxvalleypaint.com

Emergency telephone number: 1-800-255-3924

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Eye Irrit. 2A H319 Causes serious eye irritation.

Repr. 1B H360 May damage fertility or the unborn child.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.


STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: GHS Hazard pictograms









Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May damage fertility or the unborn child.

May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

Precautionary statementsObtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
	Calcium Carbonate	≥20-≤25%
	VM&P Naphtha	15-25%
	propane	10-15%
	Isopropyl Alcohol	≥5-<10%
	n-butane	5-10%
110-54-3		≥5-<10%
108-88-3		1-5%
	PM acetate	1-5%
	titanium dioxide	1-5%
67-64-1	Acetone	1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Printing date 03/26/2021 Revised On 03/26/2021

Trade name: ORANGE

After swallowing:

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

attention needed:

Rinse mouth with water. Do not induce vomiting.

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

Protective equipment for

firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures: Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure contro	ls/personal	protection
-------------------	-------------	------------

•	ontrois/personal protection		
Components with limit values that require monitoring at the workplace:			
74-98-6 propane			
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm		
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm		
TLV (USA)	refer to Appendix F inTLVs&BEIs book; D, EX		
67-63-0 Isopropyl Alcohol			
PEL (USA)	Long-term value: 980 mg/m³, 400 ppm		
REL (USA)	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm		
TLV (USA)	Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI		
106-97-8 n-butane			
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm		
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm (EX)		
110-54-3 hex			
PEL (USA)	Long-term value: 1800 mg/m³, 500 ppm		
REL (USA)	Long-term value: 180 mg/m³, 50 ppm		
TLV (USA)	Long-term value: 176 mg/m³, 50 ppm Skin; BEI		
108-88-3 Tol	108-88-3 Toluene		
PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift		
REL (USA)	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm		
TLV (USA)	Long-term value: 20 ppm BEI, NIC-OTO		
108-65-6 PM	acetate		
	Long-term value: 50 ppm		
67-64-1 Acet	one		
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm		
REL (USA)	Long-term value: 590 mg/m³, 250 ppm		
TLV (USA)	Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI		
	(Contd. on page 3)		

(Contd. of page 2)

Printing date 03/26/2021 Revised On 03/26/2021

Trade name: ORANGE

Ingredients with biological limit values:

67-63-0 Isopropyl Alcohol

BEI (USA) 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

110-54-3 hexane

BEI (USA) 0.4 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: 2.5-Hexanedione without hydrolysis

67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Store protective clothing separately. Avoid contact with the skin.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic

Odor threshold: Not determined. pH-value: Not determined.

Melting point/Melting range
Boiling point:

Flash point:

Flammability (solid, gas):

Undetermined.
-44.5 °C (-48.1 °F)
-19 °C (-2.2 °F)
Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density
Evaporation rate
Partition coefficient: n-octonal/water:
Not determined.
Not determined.
Not determined.
Not determined.
Not determined.
Not determined.

Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available.

Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

67-63-0 Isopropyl Alcohol

Oral LD50 4,570 mg/kg (rat)

(Contd. on page 4)

Safety Data Sheet

Printing date 03/26/2021 Revised On 03/26/2021

Trade name: ORANGE

(Contd. of page 3) Dermal LD50 13,400 mg/kg (rab) Inhalative LC50/4 h 30 mg/l (rat)

108-65-6 PM acetate

Oral LD50 8,500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

13463-67-7 titanium dioxide

>20,000 mg/kg (rat) Oral LD50 Dermal LD50 >10,000 mg/kg (rbt) Inhalative LC50/4 h >6.82 mg/l (rat)

Information on toxicological effects: No data available.

Skin effects: Irritant to skin and mucous membranes.

No irritating effect. Eye effects:

No sensitizing effects known. Sensitization:

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons Other information: (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available.

Harmful to fish Remark:

Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT UN1950

DOT Aerosols, flammable **ADR** 1950 AEROSOLS

Transport hazard class(es):

Class

Special precautions for user: Warning: Gases

EMS Number: F-D,S-Ŭ

Packaging Group: UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

67-63-0 Isopropyl Alcohol

110-54-3 hexane

108-88-3 Toluene

Toxic Substances Control Act

All hazardous ingredients are found on the inventory list of substances. (TSCA):

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

110-54-3 hexane

108-88-3 | Toluene

110-54-3 hexane

Ш (Contd. on page 5)

Page 5/5

Safety Data Sheet

Printing date 03/26/2021 Revised On 03/26/2021

 Trade name: ORANGE

 67-64-1 | Acetone
 (Contd. of page 4)

16 Other information

Contact: Regulatory Affairs